## <u>Images</u>

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(11) WO 2005/081609

(13) A1

- (21) PCT/JP2004/002104
- (22) 24 February 2004 (24.02.2004)
- (25) Japanese

(26) Japanese

- (43) 01 September 2005 (01.09.2005)
- (51)<sup>7</sup> H05K 9/00, H01F 1/00
- (54) ELECTROMAGNETIC WAVE NOISE SUPPRESSOR, STRUCTURAL BODY WITH ELECTROMAGNETIC WAVE NOISE SUPPRESSING FUNCTION, AND PROCESS FOR PRODUCING THEM
- (71) SHIN-ETSU POLYMER CO., LTD. [JP/JP]; 3-5, Nihonbashi-honcho 4-chome, Chuo-ku, Tokyo 103-0023 (JP).
- (71) 信越ポリマー株式会社 (SHIN-ETSU POLYMER CO., LTD.) [JP/JP]; 〒 103-0023 東京都 中央区 日本橋本町 4 丁目 3 番 5 号 Tokyo (JP).
- (72) KAWAGUCHI, Toshiyuki [JP/JP]; c/o Shin-Etsu Polymer Co., Ltd., 3-5,
- (75) Nihonbashi-honcho 4-chome, Chuo-ku, Tokyo 103-0023 (JP). **TANIGUCHI**, **Atsushi** [JP/JP]; c/o Shin-Etsu Polymer Co., Ltd., 3-5, Nihonbashi-honcho 4-chome, Chuo-ku, Tokyo 103-0023 (JP). **GONDA**, **Takashi** [JP/JP]; c/o Shin-Etsu Polymer Co., Ltd., 3-5, Nihonbashi-honcho 4-chome, Chuo-ku, Tokyo 103-0023 (JP).
- (72) 川口 利行 (KAWAGUCHI, Toshiyuki) [JP/JP]; 〒103-0023 東京都 中央区
- (75) 日本橋本町4丁目3番5号信越ポリマー株式会社内 Tokyo (JP). 谷口敦 (TANIGUCHI,Atsushi) [JP/JP]; 〒103-0023 東京都中央区日本橋本町4丁目3番5号信越ポリマー株式会社内 Tokyo (JP). 権田貴司 (GONDA,Takashi) [JP/JP]; 〒103-0023 東京都中央区日本橋本町4丁目3番5号信越ポリマー株式会社内 Tokyo (JP).
- (74) SHIGA, Masatake, et al; 2-3-1, Yaesu, Chuo-ku, Tokyo 104-8453 (JP).
- (74) 志賀 正武 (SHIGA, Masatake), et al; 〒104-8453 東京都 中央区 八重洲 2 丁目 3 番 1号 Tokyo (JP).
- (81)
  AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ,

UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(84) ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG, BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For information on time limits for entry into the national phase please click here

## **Published**

-- with international search report

(57) An electromagnetic wave noise suppressor having a magnetic resonance frequency not lower than 8 GHz, wherein the imaginary part  $\mu''_H$  of complex permeability at a frequency of 8 GHz is larger than the imaginary part  $\mu''_L$  of complex permeability at a frequency of 5 GHz. Such an electromagnetic wave noise suppressor can




exhibit sufficient electromagnetic wave noise suppression effect over the entire quasimicrowave band and can be produced by depositing a magnetic material physically on a binder (2) thereby forming a composite layer (3) on the surface of the binder (2). In the structural body with an electromagnetic wave noise suppressing function, surface of the structural body, e.g. a printed wiring board or a semiconductor integrated circuit, is coated at least partially with the electromagnetic wave noise suppressor.



Français 1 of 1